



TIKKURILA

KELLARIMAALI

DESCRIPTION

Inorganic silicate paint with excellent water vapour resistance. Waterborne.

RECOMMENDED USES

Inside walls and ceilings of cellars, garages and cold stores.

PRODUCT FEATURES

Concrete, lime, lime cement, cement plaster, sandlime brick and brick surfaces as well as mineral board surfaces indoors.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

KELLARIMAALI

TECHNICAL DATA

Colour Shades	Off white (TIKV)
Gloss	Full matt. 6/RT -classification
Coverage	approx. 3-5 m ² /l on one coat. Coverage is affected by the roughness and porosity of the surface as well as the painting method and conditions.
Can sizes	10 l
Application method	Paintbrush or roller.
Drying time	Recoatable after 12 hours.
Density (kg/l)	around 1,4 kg/l
Water vapour resistance (EN ISO 7783)	sd,H ₂ O < 0,14 m.
VOC	(cat A/a) 30g/l(2010). Kellarimaali VOC amount is max. 30 g/l.

KELLARIMAALI

APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be clean, dry and solid and the temperature of the air and surface at least +5°C and the relative humidity of the air below 80%. To avoid color differences, do not paint in strong sunlight or in the rain.

Surface preparation

Unpainted surfaces: New concrete, screed and plastered surface must be sufficiently dried and hardened before finishing treatment. Clean unpainted surfaces from dirt, dust and other impurities.

Previously painted surfaces: Clean surfaces from dirt, dust and other impurities. If necessary, clean with Tikkurila Seinäpesu cleaning agent according to instructions. Remove flaking and poorly attached or powdery paint layers. Sand well adhering paint coats until matt.

Priming

Apply one priming coat of Kellarimaali paint. The product can be thinned with water up to 10%, if necessary. After the primer has set for at least 12 hours, finishing coat will be applied.

Note

Cover surfaces that will not be treated, such as windows, natural stone or clinker-tiled surfaces and metal surfaces. Remove any paint spatter immediately with water.

The variable porous structure of the surface to be painted and moisture and temperature variations during paint application and drying may cause diversity of color.

Mechanical strain may cause visible marks on the painted surface. This is a typical product feature of matt paints; however, it does not affect the technical functionality of the product.

Cleaning of tools

Clean tools with water or Tikkurila Pensselipesu (Tool Cleaner).

Maintenance instructions

If necessary, clean the surfaces with a dry brush, mop or dust cloth after a month of the surface treatment at the earliest.

Maintenance treatment

Surface painted with Kellarimaali can be painted with same or similar product.

Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety

Contains: potassium silicate. **Danger.** Causes serious eye damage. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye or face protection. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

KELLARIMAALI



GHS05

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.